


**UNITED NATIONS / DOT
PERFORMANCE CERTIFICATION**



4G DESIGN QUALIFICATION

**6 x 1 Liter Square Plastic Bottle with Two Neck
Finish Options: #1) 38-439 Neck and #2) 45mm
Neck**

TEST REPORT #: 15-CA2077

 4G / Y13.1 / S / **
USA / +CC8458

**Insert the year packaging is manufactured

TESTING PERFORMED FOR:

PUREPAK TECHNOLOGY CORPORATION

324 South Bracken Lane Suite 3
Chandler, AZ 85224

ATTN: Michael Dodd

TESTING PERFORMED BY:

TEN-E PACKAGING SERVICES, INC.

326 North Corona Avenue
Ontario, CA 91764
Phone: 909-937-1260
Fax: 909-937-1262

May 18, 2015

TABLE OF CONTENTS

SECTION I: CERTIFICATION..... 3

SECTIONS II & V: PACKAGING DESCRIPTIONS / COMPONENT DRAWINGS 4

SECTIONS II & V: PACKAGING DESCRIPTIONS / COMPONENT DRAWINGS 5

 COMPONENT INFORMATION 6

SECTION III: TEST PROCEDURES AND RESULTS..... 9

 DROP TESTS 38-439 Neck 9

 DROP TESTS 45mm Neck 10

 STACKING & STACKING STABILITY TESTS 38-439 Neck 11

 STACKING & STACKING STABILITY TESTS 45mm Neck 12

 PRESSURE DIFFERENTIAL TEST 38-439 Neck 13

 PRESSURE DIFFERENTIAL TEST 45mm Neck..... 14

 VIBRATION TEST 38-439 Neck 15

 VIBRATION TEST 45mm Neck..... 16

 COBB WATER ABSORPTION TEST 17

REGULATORY AND INDUSTRY STANDARD REFERENCES..... 18

SECTION IV: MATHEMATICAL CALCULATIONS 38mm..... 19


SECTION IV: MATHEMATICAL CALCULATIONS 45mm..... 21

SECTION I: CERTIFICATION

**Design Qualification of the PurePak Technology Corporation
 6 x 1 Liter Square Plastic Bottle with Two Neck Finish Options:
 #1) 38-439 Neck and #2) 45mm Neck**


TEN-E Packaging Services, Inc. is a current DOT UN Third-Party Certification Agency under §107.403 and certifies that the PurePak Technology Corporation packaging referenced above has passed the standards of the DEPARTMENT OF TRANSPORTATION'S TITLE 49 CFR; Performance Oriented Packaging Standards, Section 178. This package is also certified under IMDG, ICAO/IATA Regulations and the UN Recommendations on the Transport of Dangerous Goods. It is the responsibility of the end user to determine authorization for use under these regulations. The use of other packaging methods or components other than those documented in this report may render this certification invalid.

SUMMARY OF PERFORMANCE TESTS

UN / DOT TEST	CFR REFERENCE	TEST LEVEL	TEST CONTENTS	TEST COMPLETED	TEST RESULTS
Drop	178.603	1.9 m	Methanol/Water	May 14, 2015	PASS
Stacking	178.606	544.3 Kg – 24 Hours	Water	May 18, 2015	PASS
Pressure	173.27	100 kPa - 30 Minutes	Water	May 18, 2015	PASS
Vibration	178.608	3.6 Hz – 1 Hour	Water	May 14, 2015	PASS
Cobb	178.516	30 Minutes	---	May 12, 2015	PASS
TEST REPORT NUMBER:		15-CA20077			
UN MARKING: (CFR 49 – 178.503)		 4G / Y13.1 / S / ** USA / +CC8458			
PACKAGING IDENTIFICATION CODE:		4G - Fiberboard Box (178.516)			
PERFORMANCE STANDARD:		Y (Packaging meets Packing Group II and III tests)			
AUTHORIZED GROSS MASS:		13.1 Kg (28.8 Lbs)			
"S" DESIGNATION:		Denotes Inner Packagings			
YEAR OF MANUFACTURE:		** Insert year the packaging is manufactured			
STATE AUTHORIZING THE MARK		USA			
PACKAGING CERTIFICATION AGENCY:		(+CC) TEN-E Packaging Services, Inc. (Ontario CA #2006030021)			
THIRD PARTY PACKAGING IDENTIFICATION:		+CC8458			
PERIODIC RETEST DATE:		May 18, 2017			


ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY THAT THE PACKAGING TESTED IS MERCHANTABLE OR FIT FOR A PARTICULAR PURPOSE, ARE DISCLAIMED. In no event shall TEN-E Packaging Services, Inc. liability exceed the total amount paid by PurePak Technology Corporation for services rendered. In the event of future changes to the above referenced test standards, it is the responsibility of PurePak Technology Corporation to determine whether additional testing or updating of past testing is necessary to verify that the packaging we have tested remains in compliance with those standards.

MANUFACTURER:
 PurePak Technology Corporation
 324 South Bracken Lane Suite 3
 Chandler, AZ 85224


 Matt C. Anderson
 Project Manager
 TEN-E Packaging Services, Inc.


SECTIONS II & V: PACKAGING DESCRIPTIONS / COMPONENT DRAWINGS

6 x 1 Liter Square Plastic Bottle with 38-439 Neck



ASSEMBLY DRAWING	TEST LEVELS		
	Certification Type:	Design Qualification	
	Packaging Code Designation:	4G	
	Packing Group:	II	
	Specific Gravity:	1.9	
	Internal Pressure:	100 kPa	
	TEST SAMPLE PREPARATION (Refer to Section IV)		
	Overall Packaging Tare Weight:	992.0 Grams	
	Fill Capacity (98% Maximum Capacity):		
	Methanol/Water	1,032.0 Grams	
	Water	1,067.3 Grams	
	Package Test Weight:		
	Methanol/Water	7.1 Kg	15.6 Lbs
	Water	7.3 Kg	16.0 Lbs
	Authorized Package Gross Mass:	13.1 Kg	28.8 Lbs
	CLOSING METHODS – INNER PACKAGING		
	Application Torque:	50 In-Lbs	
	Equipment:	Kaps All Electronic Torque Tester	
	CLOSING METHODS – SHIPPER		
	Top Flaps:		
	Manufacturer:	3M: St. Paul, MN	
Type:	Scotch 3M Pressure Sensitive Tape		
Width:	48 mm (2")		
Overlap:	2" Minimum		
Tape Pattern:	Center Seam		
Inner Flaps:	4" Width Gap		
Outer Flaps:	Meet		
Bottom Flaps:			
Manufacturer:	3M: St. Paul, MN		
Type:	Scotch 3M Pressure Sensitive Tape		
Width:	48 mm (2")		
Overlap:	2" Minimum		
Tape Pattern:	Center Seam		
Inner Flaps:	4" Width Gap		
Outer Flaps:	Meet		

SECTIONS II & V: PACKAGING DESCRIPTIONS / COMPONENT DRAWINGS

6 x 1 Liter Square Plastic Bottle with 45mm Neck

ASSEMBLY DRAWING	TEST LEVELS	
	Certification Type:	Design Qualification
	Packaging Code Designation:	4G
Packing Group:	II	
Specific Gravity:	1.9	
Internal Pressure:	100 kPa	
TEST SAMPLE PREPARATION (Refer to Section IV)		
Overall Packaging Tare Weight:	995.0 Grams	
Fill Capacity (98% Maximum Capacity):		
Methanol/Water	1,056.0 Grams	
Water	1,092.7 Grams	
Package Test Weight:		
Methanol/Water	7.3 Kg	16.0 Lbs
Water	7.5 Kg	16.5 Lbs
Authorized Package Gross Mass:	13.4 Kg	29.5 Lbs
CLOSING METHODS – INNER PACKAGING		
Application Torque:	25 In-Lbs	
Equipment:	Kaps All Electronic Torque Tester	
CLOSING METHODS – SHIPPER		
Top Flaps:		
Manufacturer:	3M: St. Paul, MN	
Type:	Scotch 3M Pressure Sensitive Tape	
Width:	48 mm (2")	
Overlap:	2" Minimum	
Tape Pattern:	Center Seam	
Inner Flaps:	4" Width Gap	
Outer Flaps:	Meet	
Bottom Flaps:		
Manufacturer:	3M: St. Paul, MN	
Type:	Scotch 3M Pressure Sensitive Tape	
Width:	48 mm (2")	
Overlap:	2" Minimum	
Tape Pattern:	Center Seam	
Inner Flaps:	4" Width Gap	
Outer Flaps:	Meet	

COMPONENT INFORMATION

CLOSURE		DRAWING
Manufacturer: Rexam Plastic Packaging: Evansville, IN (QIM-317-4937)		
Description:	38mm Threaded Closure	
Quantity:	6	
Material:	Polypropylene	
Tare Weight:	10.03 Grams	
Overall Dimensions:		
• Height	1.016" ± 0.015"	
• Diameter	1.701" ± 0.015"	
Thread:		
• Type	38mm	
• Style	439	
Finish Dimensions:		
• T	1.483" ± 0.007"	
• E	1.389" ± 0.007"	
Markings (QC Audit):	6	
Liner:		
Description:	P.E. Foam Liner	
Tare Weight:	0.68 Grams	
Thickness:	0.052"	
Diameter:	1.377"	
PLASTIC BOTTLE		DRAWING
Manufacturer: Berry Plastics: Evansville, IN (Job #: ZB38SQ1H)		
Description:	1 Liter Square Plastic Bottle	
Quantity:	6	
Material/Pigment:	High Density Polyethylene / Natural	
Method of Manufacture:	Blow Molded	
Tare Weight:	85 Grams ± 4.25 Grams	
Capacity:		
• Rated	1 Liter	
• Overflow	1,089.0 Grams (36.8 Oz)	
Overall Dimensions:		
• Height	6.929" ± 0.070"	
• Width	4.010" ± 0.060"	
• Depth	4.010" ± 0.060"	
Thread Dimensions:		
• T	1.461" ± 0.010"	
• E	1.367" ± 0.010"	
Wall Thickness:		
• Minimum	0.028"	
Markings (QC Audit):	SPI "2" HDPE Recycling Symbol 1 2/14	

CLOSURE		DRAWING
Manufacturer: George MENSHEN GmbH: Finnentrop, Germany (4.1451.99.2)		
Description:	45mm Tamper Evident Threaded Closure	
Quantity:	6	
Material:	High Density Polyethylene	
Tare Weight:	11.07 Grams	
Overall Dimensions:		
• Height	30.3mm	
• Diameter	2.002"	
Thread:		
• Type	45mm	
Finish Dimensions:		
• T	1.792"	
• E	1.356"	
Markings (QC Audit):	1451 6	
Liner:		
Description:	KER45 PTFE Plug	
Tare Weight:	0.92 Grams	
Thickness:	0.0094"	
Diameter:	1.797	
PLASTIC BOTTLE		
Manufacturer: Berry Plastics: Evansville, IN (Job #: Z45SQ1H)		
Description:	1 Liter Square Plastic Bottle	
Quantity:	6	
Material/Pigment:	High Density Polyethylene / Natural	
Method of Manufacture:	Blow Molded	
Tare Weight:	85 Grams ± 4.25 Grams	
Capacity:		
• Rated	1 Liter	
• Overflow	1,115.0 Grams (37.6 Oz)	
Overall Dimensions:		
• Height	6.963" ± 0.060"	
• Width	3.972" ± 0.060"	
• Depth	3.972" ± 0.060"	
Thread Dimensions:		
• T	1.772" ± 0.010"	
• E	1.644" ± 0.010"	
Wall Thickness:		
• Minimum	0.033"	
Markings (QC Audit):	SPI "2" HDPE Recycling Symbol 1 9/13	

SHIPPER		
Manufacturer: Sound Packaging: Chandler, AZ		
Description:	Regular Slotted Container	
Material/Flute (Inner to Outer):	275 Lb Test Double Wall Natural Kraft Corrugated Fiberboard; B/C-Flute	
Basis Weight (Outer to Inner) Lbs./MSF:		
• Specification	42/23/26/23/42	
Tare Weight:	417 Grams	
DIMENSIONS		
	Specification Dimensions (Inside)	Measured Dimensions (Outside)
• Length	12"	12-1/2"
• Width	8-1/16"	8-3/4"
• Height	7-1/8"	8-3/8"
Board Caliper (Nominal):	0.255"	
Manufacturer's Joint:	Inside Glued, 1-3/8" Lap	
Markings (QC Audit):	NONE	







SECTION III: TEST PROCEDURES AND RESULTS

DROP TESTS

38-439 Neck

TEST INFORMATION		TEST CRITERIA
TEST CONTENTS:	Methanol/Water Solution (0.967 SG)	<ul style="list-style-type: none"> For packaging containing liquid, each packaging does not leak. There can be no damage to the outer packaging likely to adversely affect safety during transport. Inner receptacles, inner packagings or articles must remain completely within the outer packaging and there must be no leakage of the filling substance from the inner packaging. Any discharge from a closure is slight and ceases immediately after impact with no further leakage. No rupture is permitted in packagings for materials in Class 1 which would permit spillage of loose explosive substances or articles from the outer packaging. (\$178.603)
SAMPLE PREPARATION:	Refer to Section II	
CONDITIONING:	-18°C (0°F) Freezer #201	
CONTENTS TEMP.:	-18.3°C (-1.0°F)	
DROP HEIGHT:	1.9 Meters (75") (Refer to Section IV)	
TEST EQUIPMENT:	L.A.B. Accu Drop 160	

DROP ORIENTATIONS AND TEST RESULTS

Sample #1: Flat on Bottom	Sample #2: Flat on Top	*Sample #3: Flat on Long Side
		
PASS: No leakage or damage.	PASS: No leakage or damage.	PASS: No leakage or damage.
*Sample #4: Flat on Short Side	*Sample #5: Bottom Corner	**Sample #1: Top Corner
		
PASS: No leakage or damage.	PASS: No leakage. Deformation to shipper on impact.	PASS: No leakage. Deformation to shipper on impact.

*Side and corner drops were conducted to impact the manufacturer's joint







** Flat on Bottom Drop sample was also used for the Top Corner drop.

DROP TESTS

45mm Neck

TEST INFORMATION		TEST CRITERIA
TEST CONTENTS:	Methanol/Water Solution (0.967 SG)	<ul style="list-style-type: none"> For packaging containing liquid, each packaging does not leak. There can be no damage to the outer packaging likely to adversely affect safety during transport. Inner receptacles, inner packagings or articles must remain completely within the outer packaging and there must be no leakage of the filling substance from the inner packaging. Any discharge from a closure is slight and ceases immediately after impact with no further leakage. No rupture is permitted in packagings for materials in Class 1 which would permit spillage of loose explosive substances or articles from the outer packaging. (§178.603)
SAMPLE PREPARATION:	Refer to Section II	
CONDITIONING:	-18°C (0°F) Freezer #201	
CONTENTS TEMP.:	-18.3°C (-1.0°F)	
DROP HEIGHT:	1.9 Meters (75") (Refer to Section IV)	
TEST EQUIPMENT:	L.A.B. Accu Drop 160	

DROP ORIENTATIONS AND TEST RESULTS

Sample #12: Flat on Bottom	Sample #13: Flat on Top	*Sample #14: Flat on Long Side
		
PASS: No leakage or damage.	PASS: No leakage or damage.	PASS: No leakage or damage.
*Sample #15: Flat on Short Side	*Sample #16: Bottom Corner	**Sample #12: Top Corner
		
PASS: No leakage or damage.	PASS: No leakage. Deformation to shipper on impact.	PASS: No leakage. Deformation to shipper on impact.


*Side and corner drops were conducted to impact the manufacturer's joint


** Flat on Bottom Drop sample was also used for the Top Corner drop.

STACKING & STACKING STABILITY TESTS

38-439 Neck

TEST INFORMATION		TEST CRITERIA
TEST CONTENTS:	Water	<ul style="list-style-type: none"> • There must be no leakage of the filling substance from the inner receptacle, or inner packaging. • There can be no deterioration that could adversely affect transport safety or any distortion liable to reduce the package's strength, cause instability in stacks of packages, or cause damage to inner packagings that is likely to reduce safety in transport. <p>(§178.606)</p>
SAMPLE PREPARATION:	Refer to Section II	
CONDITIONING:	73°F / 50% RH Quality Room #202	
TEST LOAD APPLIED:	544.3 Kg (1,200.0 Lbs) (Refer to Section IV)	
TEST DURATION:	24 Hours	
TEST EQUIPMENT:	L.A.B. Validator Plus Compression System	

STACKING TEST SET-UP & RESULTS			
	Sample #	Maximum Deflection After 24 Hours	Results
	6	0.078"	PASS
	7	0.078"	PASS
	8	0.078"	PASS
	Comments/Observations		
<p>Following the stack test there was no leakage or damage likely to result in failure of the packaging.</p>			


STACKING STABILITY TEST SET-UP & RESULTS		
	Results	CRITERIA FOR PASSING THE TEST
	PASS	<ul style="list-style-type: none"> • In guided load tests, stacking stability must be assessed after test completion. • Two filled packagings of the same type must be placed on the test sample. • The stacked packages must maintain their position for one hour. <p>(§178.606)</p>
<p>For stack stability, TEN-E places the filled samples one on top of the other. The bottom sample is rotated to the top until all three samples have been subjected to stacking stability for one hour each.</p>		

STACKING & STACKING STABILITY TESTS


45mm Neck

TEST INFORMATION		TEST CRITERIA
TEST CONTENTS:	Water	<ul style="list-style-type: none"> • There must be no leakage of the filling substance from the inner receptacle, or inner packaging. • There can be no deterioration that could adversely affect transport safety or any distortion liable to reduce the package's strength, cause instability in stacks of packages, or cause damage to inner packagings that is likely to reduce safety in transport. <p>(§178.606)</p>
SAMPLE PREPARATION:	Refer to Section II	
CONDITIONING:	73°F / 50% RH Quality Room #202	
TEST LOAD APPLIED:	544.3 Kg (1,200.0 Lbs) (Refer to Section IV)	
TEST DURATION:	24 Hours	
TEST EQUIPMENT:	L.A.B. 5250 Compression System	

STACKING TEST SET-UP & RESULTS

	Sample #	Maximum Deflection After 24 Hours	Results
	13	0.078"	PASS
	14	0.078"	PASS
	15	0.078"	PASS
Comments/Observations			
Following the stack test there was no leakage or damage likely to result in failure of the packaging.			

STACKING STABILITY TEST SET-UP & RESULTS


	Results	CRITERIA FOR PASSING THE TEST
	PASS	<ul style="list-style-type: none"> • In guided load tests, stacking stability must be assessed after test completion. • Two filled packagings of the same type must be placed on the test sample. • The stacked packages must maintain their position for one hour. <p>(§178.606)</p>
For stack stability, TEN-E places the filled samples one on top of the other. The bottom sample is rotated to the top until all three samples have been subjected to stacking stability for one hour each.		

PRESSURE DIFFERENTIAL TEST

38-439 Neck

TEST INFORMATION		TEST CRITERIA
TEST CONTENTS:	Water	<ul style="list-style-type: none"> • Packaging for which retention of liquid is a basic function must be capable of withstanding the pressure requirements without leakage. (§173.27(c))
FILL CAPACITY:	Maximum Capacity	
CLOSURE APPLICATION:	Refer to Section II	
CONDITIONING:	Ambient	
TEST PRESSURE:	100 kPa	
TEST DURATION:	30 Minutes	
AREA OF PRESSURIZATION:	Through the Bottom	
TEST EQUIPMENT:	Regulated Water Source Digital Pressure Gauge	

HYDROSTATIC PRESSURE TEST SET-UP AND RESULTS


	Sample #	Results	Comments/Observations
	1	PASS	All three samples maintained the 100 kPa test pressure for 30 minutes without leakage or damage.
	2	PASS	
	3	PASS	

PRESSURE DIFFERENTIAL TEST

45mm Neck

TEST INFORMATION		TEST CRITERIA
TEST CONTENTS:	Water	<ul style="list-style-type: none"> • Packaging for which retention of liquid is a basic function must be capable of withstanding the pressure requirements without leakage. (§173.27(c))
FILL CAPACITY:	Maximum Capacity	
CLOSURE APPLICATION:	Refer to Section II	
CONDITIONING:	Ambient	
TEST PRESSURE:	100 kPa	
TEST DURATION:	30 Minutes	
AREA OF PRESSURIZATION:	Through the Bottom	
TEST EQUIPMENT:	Regulated Water Source Digital Pressure Gauge	

HYDROSTATIC PRESSURE TEST SET-UP AND RESULTS


	Sample #	Results	Comments/Observations
	1	PASS	All three samples maintained the 100 kPa test pressure for 30 minutes without leakage or damage.
	2	PASS	
	3	PASS	

VIBRATION TEST

38-439 Neck

TEST INFORMATION		TEST CRITERIA
TEST CONTENTS:	Water	<ul style="list-style-type: none"> Immediately following the period of vibration, each package must be removed from the platform, turned on its side and observed for any evidence of leakage. A packaging passes the vibration test if there is no rupture or leakage from any of the packages. No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength. <p>(§178.608)</p>
SAMPLE PREPARATION:	Refer to Section II	
CONDITIONING:	73°F / 50% RH Quality Room #202	
TABLE DISPLACEMENT:	1"	
TEST FREQUENCY:	3.6 Hz	
TEST DURATION:	1 Hour	
TEST EQUIPMENT:	Vertical motion using L.A.B. Palletizer Vibration System	

VIBRATION TEST SET-UP AND RESULTS


	Sample #	Results	Comments/Observations
	9	PASS	No leakage or damage.
	10	PASS	
	11	PASS	

VIBRATION TEST

45mm Neck

TEST INFORMATION		TEST CRITERIA
TEST CONTENTS:	Water	<ul style="list-style-type: none"> Immediately following the period of vibration, each package must be removed from the platform, turned on its side and observed for any evidence of leakage. A packaging passes the vibration test if there is no rupture or leakage from any of the packages. No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength. (§178.608)
SAMPLE PREPARATION:	Refer to Section II	
CONDITIONING:	73°F / 50% RH Quality Room #202	
TABLE DISPLACEMENT:	1"	
TEST FREQUENCY:	3.6 Hz	
TEST DURATION:	1 Hour	
TEST EQUIPMENT:	Vertical motion using L.A.B. Palletizer Vibration System	

VIBRATION TEST SET-UP AND RESULTS

	Sample #	Results	Comments/Observations
	16	PASS	No leakage or damage.
	17	PASS	
	18	PASS	

COBB WATER ABSORPTION TEST

TEST INFORMATION	TEST CRITERIA
<p>NUMBER OF SAMPLES: 5</p> <p>SAMPLE SIZE: 5" x 5" (Minimum)</p> <p>CONDITIONING: 73°F / 50% RH Quality Room #202</p> <p>WATER APPLIED: 100 mL / Sample</p> <p>TEST DURATION: 30 Minutes / Sample</p> <p>TEST EQUIPMENT: UWE Analytical Balance Gurley Cobb Water Absorption Fixtures</p>	<ul style="list-style-type: none"> An increase in mass greater than 155 g/m² over the 30 minute duration represents an unacceptable level of water resistance. (§178.516)

COBB WATER ABSORPTION TEST RESULTS	
Sample #	Water Absorbed
1	125 g/m ²
2	127 g/m ²
3	124 g/m ²
4	134 g/m ²
5	149 g/m ²
AVERAGE:	131.8 g/m²
RESULT	PASS

REGULATORY AND INDUSTRY STANDARD REFERENCES

REGULATORY REFERENCES

TEST	49 CFR ^①	UN ^②	IMDG ^③	ICAO ^④	IATA ^⑤
	October 2014 Edition	18 th Edition	2014 Edition	2015-2016 Edition	56th Edition
Drop:	178.603	6.1.5.3	6.1.5.3	6; 4.3	6.3.3
Stacking:	178.606	6.1.5.6	6.1.5.6	6; 4.6	6.3.6
Pressure:	173.27(c)	4.1.1.4.1	4.1.1.4.1	4; 1.1.6	5.0.2.9
Vibration:	178.608	---	---	4; 1.1.1	5.0.2.7
Cobb:	178.516(b)(1)	6.1.4.12.1	6.1.4.12.1	6; 3.1.11.1	6.2.12.2

- ① United States Department of Transportation Code of Federal Regulations (CFR) Title 49, Transportation, Parts 100-185
 ② The United Nations Recommendations on the Transport of Dangerous Goods – Model Regulations (UN – Orange Book)
 ③ International Maritime Dangerous Goods Code (IMDG)
 ④ Technical Instructions for the Safe Transport of Dangerous Good by Air (ICAO)
 ⑤ International Air Transport Association (IATA) Dangerous Goods Regulations

INDUSTRY STANDARD REFERENCES

Drop:	ASTM ^⑥ D5276:	Standard Test Method for Drop Test of Loaded Containers by Free Fall
	ASTM ^④ D7790	Standard Test Method for the Preparation of Plastic Packagings Containing Liquids for United Nations (UN) Drop Testing
	ISO ^⑦ 2248:	Packaging – Complete, Filled Transport Packages – Vertical Impact Test by Dropping
Stacking:	ASTM ^⑥ D4577:	Standard Test Method for Compression Resistance of a Container Under Constant Load
	ISO ^⑦ 2234:	Packaging – Complete, Filled Transport Packages – Stacking Test using Static Load
Hydrostatic Pressure:	ASTM ^⑥ D7660:	Standard Guide for Conducting Internal Pressure Tests on United Nations (UN) Packagings
Vibration:	ASTM ^⑥ D999:	Standard Test Method for Vibration Testing of Shipping Containers
	ISO ^⑦ 2247:	Packaging – Complete, Filled Transport Packages – Vibration Test at Fixed Low Frequency
Cobb:	ISO ^⑦ 535:	Paper and Board – Determination of Water Absorption – Cobb Method

- ⑥ American Society for Testing and Materials (ASTM)
 ⑦ International Organization for Standardization (ISO)

EQUIPMENT

All inspection, measuring and test equipment that can affect product quality is calibrated and adjusted at prescribed intervals, or prior to use, and is traceable to NIST, using ANSI Z540 as an overall guide for calibration certification.

SECTION IV: MATHEMATICAL CALCULATIONS

38mm

INFORMATION USED FOR CALCULATIONS

Overall Packaging Tare Weight (PTW):	992.0 Grams	
Overflow Capacity (OFC):		Methanol/Water SG
Methanol/Water	1,053.0 Grams	SG: 0.967
Water	1,089.0 Grams	
Number of Inner Packagings (# IP):	6	
Packing Group	II	
Product Specific Gravity (PSG):	1.900	
Packing Group Multiplication Factor (MF):	1.00	
Overall Height of one Package (OH):	8.38 Inches	
Stack Test-# of Samples Tested Simultaneously:	3	

98% OF OVERFLOW

Overflow Capacity (OFC) x 98%

<u>OFC</u>	x	<u>98%</u>		
1,053.0	x	98% =	1,032.0 Grams	Methanol/Water
1,089.0	x	98% =	1,067.3 Grams	Water

PACKAGE TEST WEIGHTS

Overall Pkg Tare Weight (PTW) + (98% Overflow Capacity (OFC) x # of Inner Pkg (# IP))

<u>PTW</u>	+	<u>(98% OFC)</u>	x	<u># IP)</u>	
992	+	1,032.0	x	6	Methanol/Water
992	+	1,067.3	x	6	Water
Methanol/Water:		7.1	Kg	15.6	Lbs.
Water:		7.3	Kg	16.0	Lbs.

AUTHORIZED PACKAGE GROSS MASS CALCULATION (APGM)

Overall Pkg Tare Weight (PTW) + (Product SG (PSG) x 98% Overflow (OFC) x # of Inner Pkg (# IP))

<u>PTW</u>	+	<u>(PSG)</u>	x	<u>98% OFC</u>	x	<u># IP)</u>
992	+	1.9	x	1,067	x	6
		13.1	Kg	28.8	Lbs.	

SECTION IV: MATHEMATICAL CALCULATIONS

45mm

INFORMATION USED FOR CALCULATIONS

Overall Packaging Tare Weight (PTW):	995.0 Grams	
Overflow Capacity (OFC):		Methanol/Water SG
Methanol/Water	1,078.2 Grams	SG: 0.967
Water	1,115.0 Grams	
Number of Inner Packagings (# IP):	6	
Packing Group	II	
Product Specific Gravity (PSG):	1.900	
Packing Group Multiplication Factor (MF):	1.00	
Overall Height of one Package (OH):	8.38 Inches	
Stack Test-# of Samples Tested Simultaneously:	3	

98% OF OVERFLOW

Overflow Capacity (OFC) x 98%

<u>OFC</u>	x	<u>98%</u>		
1,078.2	x	98% =	1,056.7 Grams	Methanol/Water
1,115.0	x	98% =	1,092.7 Grams	Water

PACKAGE TEST WEIGHTS

Overall Pkg Tare Weight (PTW) + (98% Overflow Capacity (OFC) x # of Inner Pkg (# IP))

<u>PTW</u>	+	<u>(98% OFC)</u>	x	<u># IP)</u>	
995	+	1,056.7	x	6	Methanol/Water
995	+	1,092.7	x	6	Water
Methanol/Water:		7.3	Kg	16.0	Lbs.
Water:		7.5	Kg	16.5	Lbs.

AUTHORIZED PACKAGE GROSS MASS CALCULATION (APGM)

Overall Pkg Tare Weight (PTW) + (Product SG (PSG) x 98% Overflow (OFC) x # of Inner Pkg (# IP))

<u>PTW</u>	+	<u>(PSG)</u>	x	<u>98% OFC</u>	x	<u># IP)</u>
995	+	1.9	x	1,093	x	6
		13.4	Kg	29.5	Lbs.	

